



## Product Specification

Product Name: **SYDNEY HARBOUR'S CHALKBOARD PAINT**

---

### PRODUCT DESCRIPTION:

Sydney Harbour's Chalkboard Paint is perfect for making your own chalkboards in cafés, kitchens, workplaces and children's play areas. Available in two bases, traditional Black, and also Ultra Deep for a fun range of bright bold colours. Dries to a smooth finish for easy cleaning. Has a superb creamy texture, excellent coverage and is Low Odour.

### LOCATION:

Interior or exterior.

### ENVIRONMENTAL INFORMATION:

This product contains: 28g/L VOC.

APAS\* Target level for this product: 100g/L.

Sydney Harbour Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

\* Australian Paint Approval Scheme.

### SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

### COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

### LIMITATIONS:

Do not apply in high humidity, below 50°F or above 86°F.

### PREPARATION:

#### NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding.

On bare surfaces such as new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with

Sydney Harbour's Limeproof Undercoat Sealer, then apply two coats of same to entire area.

#### PREVIOUSLY PAINTED SUBSTRATES:

Provided the surface is clean and sound, Sydney Harbour's Chalkboard Paint can be applied directly over previously painted surfaces.

Previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Sydney Harbour's Limeproof Undercoat Sealer, then apply one coat to entire area. Touch dry two hours. Allow 6 hours dry time.

#### APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush or a medium nap roller. Touch dry in 30 minutes. Allow minimum 2 hours dry time between coats. Allow 48 hours dry time before use as a chalkboard.

#### CARE OF YOUR CHALKBOARD

Chalk can be removed with ordinary blackboard dusters, however, for best results clean with a damp sponge or rag.

#### COVERAGE RATES:

Covers approximately 350 sq ft per gallon, depending upon porosity, surface texture and wastage rates.

#### WASH UP:

Water.

#### COMPLEMENTARY PRODUCTS:

Sydney Harbour's Limeproof Undercoat Sealer (coverage 400-450ft<sup>2</sup> per gallon) is recommended where an undercoat/primer is required when preparing substrate for painting.

#### PACKAGING:

Sydney Harbour's Chalkboard Paint is available in Quart & Gallon sizes.

#### STORAGE:

Store in a cool dry area, protected from frost.

#### PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

#### WARRANTY:

Sydney Harbour's Chalkboard Paint has a warranty of 7 years. Porter's Paints Pty Ltd warrants this product to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the

supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

#### **MANUFACTURER'S/DISTRIBUTOR'S DETAILS:**

Distributor:

Sydney Harbour Paint Company

18424 Ventura Boulevard

Los Angeles, CA 91356

Phone: (213)291-1586

Fax: (818) 641-1119

Web: [www.sydneyharbourpaints.com](http://www.sydneyharbourpaints.com)

Porter's Paints Pty Ltd

895 Bourke St

Waterloo NSW 2017

Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)

Web: [www.porterspains.com](http://www.porterspains.com)