

# **PRODUCT**

# ACRYLIC CRACKLE GLAZE

**DESCRIPTION** 

An Acrylic medium to produce consistent cracking of emulsion paint/latex.

<u>SHEEN LEVEL</u> N/A

<u>CONTAINERS</u> 300ml, 1L, 10.0 fl oz, US Quart.

## APPLICATION

Seal porous surfaces; ensure product is well mixed.

Always try the technique on a test piece before starting the project. Walls and vertical surfaces need a lot of practice. Choose the colour of matt emulsion/latex paint, one for the base coat - the colour of the cracks, the other for the topcoat.

Apply the base coat and allow to dry. Apply the crackle glaze in one direction with a good quality brush. The coat must be smooth and even, if not remove the glaze with a damp cloth, and reapply working it into the surface before laying off to a smooth even coat. Apply the topcoat of **matt** emulsion/latex, thinned with 10% water to produce an easily flowing paint. Apply at right angles to the crackle glaze coat. Lay off with a good quality brush, load brush with generous amount of paint and apply in one pass only. Do not over brush this will mix the glaze and paint and no cracks will appear. The thickness of the topcoat determines the size of the cracks – the thicker the coat the wider the cracks. Leave to dry for 24 hours and protect with Polyvine Decorators Varnish

<u>USES</u> Furniture. Woodwork. Plaster work. Non Ferrous metals.

<u>COVERAGE</u> Approx. 8 sq. m per litre 85 sq. ft per US qt

<u>No OF COATS</u> 1 coat

DRYING TIME 15mins-1 hr, depending on temperature

## RECOAT TIME N/A

<u>CURING</u> N/A

#### **CLEANING**

Clean tools/equipment with warm soapy water, rinse well with clean water, and allow to dry naturally.

FLAMMABILITY No fire hazard before or during use, or in the cured state.

<u>STORAGE</u> Protect from extremes of temperature during storage and application.

## HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best if our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to access the suitability of the product on a test area before application

POLYVINE LTD Tel: 0845 017 1671 Fax: 0845 017 1670 Website <u>www.polyvine.co.uk</u> E-mail info@polyvine.co.uk