



Product Specification

Product Name: **SYDNEY HARBOUR'S MATT WALL SEALER**

PRODUCT DESCRIPTION:

Sydney Harbour's Matt Wall Sealer is an interior use product that is recommended as a protective clear sealer specifically designed for use over Sydney Harbour's Interno, Sydney Harbour's Interior Distemper, Sydney Harbour's Lime Wash or Boncote Cement Paint (when used on a interior surface). Allows these surfaces to resist marking and staining, makes these matt decorative finishes wipeable.

When recoating Interno or Distemper that has been protected with Matt Wall Sealer, Matt Wall Sealer can be painted over directly without the need to begin again with an undercoat.

LOCATION:

Interior.

ENVIRONMENTAL INFORMATION:

This product contains: 7g/L VOC.

APAS* Target level for this product: 75g/L.

Although this product is unique and there is no comparative product type, the closest comparison would be a typical water-based interior low sheen paint that has a VOC level of approx. 75g/L

Sydney Harbour Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

Suitable for use as a protective clear sealer for use over Sydney Harbour's Interno, Interior Distemper, Sydney Harbour's Lime Wash and Boncote Cement Paint (interior) only.

COLOUR:

Appears milky white in can, dries clear.

LIMITATIONS:

Do not apply in high humidity, below 50°F or above 86°F. Allow paints to cure for a minimum of 7 days before application. Over saturation whilst applying Matt Wall Sealer, or a substrate which is not completely dry, may cause white markings to appear on a surface. Avoid dribbles or runs as these will remain evident when dry. Test before use as a slight colour variation may occur.

PREPARATION:

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil and mould. Dust down before proceeding. Allow all paints and finishes to a dry a minimum of 7 days prior to the application of Sydney Harbour's Matt Wall Sealer.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush in a random or "crows feet" method. Touch dry in 2 hours. Allow minimum 6 hours dry time between coats. Allow to dry 6 hours.

COVERAGE RATES:

Covers approximately 600-650ft² per gallon; depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

PACKAGING:

Sydney Harbour's Matt Wall Sealer is available in 1 litre, 4 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

WARRANTY:

Sydney Harbour's Matt Wall Sealer has a warranty for 7 years. Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Distributor:

Sydney Harbour Paint Company

18424 Ventura Boulevard

Los Angeles, CA 91356

Phone: (213)291-1586

Fax: (818) 641-1119

Web: www.sydneyharbourpaints.com

Porter's Paints Pty Ltd
895 Bourke St
Waterloo NSW 2017
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com